




SeaHawk LD2100

The LD2100 is a robust, Web-accessible distance read leak detection controller. When integrated with SeaHawk leak detection cable (sensing cable) or spot detectors, the LD2100 detects the presence of fluids and reports the distance to the leak. Within seconds, the distance to the leak is shown on the LED display. The physical location of the leak can then be determined by viewing the interactive map in the user interface or by cross referencing the distance on the display with a wall map.

The LD2100 has an audible alarm for local monitoring. In addition, it can easily integrate into existing building management, network management, and building automation systems, or be configured for direct alarm notification via email.

Common applications include data centers, clean rooms, telecommunication centers, and other critical areas. The LD2100 offers a reliable leak detection solution that mitigates potential damage, costly business outages, and downtime.



Uploaded reference map can be configured to display the location of the leak

Features

- Interactive leak detection map
- Quick return to normal status after sensing cable is wiped dry
- Adjustable leak, delay, and contamination thresholds
- Thirty-two configurable zones
- SNMP, Modbus, BACnet, and summary relay output
- SMTP (email) notification of alarm conditions
- Audible alarm

Benefits

- Easy identification of leak location
- Helps avoid costly damage and downtime by notifying of leaks quickly
- Prevents nuisance & false alarms
- Allows users to label unique areas for quick identification
- Simple integration with BMS, NMS & BAS
- No factory calibration required
- Identifies cable disconnects & breaks
- Annunciates multiple, simultaneous leaks when other distance read controllers are integrated into the system

Leak Detection

LD2100 Specifications

Power	24VDC@ 600mA max., 50/60Hz; requires power supply: PSWA-DC-24 (not included) 24VAC Isolated@ 600mA max., 50/60Hz; requires power supply (not included) 100/120/230-240VAC@ 500mA max., 50/60Hz power supply; included in the LD-ENC optional enclosure
Accessories	Leader cable and EOL terminator (LC-KIT; included), caution tags (SC-T), framed reference map (FM1114), leak detection cable (sensing cable; SC-xx), non-sensing cable (NSC-xx), spot detector (SD-Z), X-Connector for cable branching (X-CON), weighted cable connector (WCCS-50), J-Clips for securing cable (JC-xx)
Output	
Relay	1 Form C summary relay, 1A @ 24VDC, 0.5A resistive @ 120VAC; configurable for latched or non-latched
Inputs	
Leak Detection Cable	Compatible with SeaHawk sensing cables (not included)
Cable Input	Requires 15ft (4.57m) leader cable and EOL terminator (LC-KIT; included)
Maximum Length	5,000ft (1524m)
Minimum Length	35 ft. (10.67m)
Detection Accuracy	± 2ft (0.6m) +/- 0.25% of the cable length
Detection Repeatability	5-995sec, software adjustable in 5sec increments; ±2sec
Detection Response Time	
Communication Ports	
Ethernet	10/100BaseT, full/half duplex RJ45 connector; 500VAC RMS isolation
EIA-232	DB9 female connector; 9600 baud; 8 data bits, no parity, 1 stop bit
EIA-485	9600, 19200, 38400, or 56700 baud (selectable); Parity: none, even or odd, 8 data bits, 1 stop bit
Protocols	
TCP/IP, HTML, TFTP	IPv4.0; webpages comply with Rehabilitation Act of 1973, sections 504 and 508, US Dept of Education (website accessibility for computer users with disabilities)
SNMP	V1: V2C MIB-2 compliant; NMS Manageable with Get, Set, Traps
SMTP (Email)	Supports Client Authentication (plain and login); compatible with ESMTP Servers
Modbus (EIA-485)	Slave; RTU mode; Supports function codes 03, 04, 06 and 16 Master: RTU mode for integration with RLE's LD5100, LD2100, LD2000, and LD1500 products only; Johnson N2
Modbus TCP/IP UDP/IP	Modbus Slave; TCP/IP transmission protocol Modbus Master; TCP/IP transmission protocol for integration with RLE's LD2100, LD2000, and LD1500 products only
BACnet/IP	ASHRAE STD 135-2004 Annex J
BACnet MS/TP	EIA-485
BACnet Alarms	Automatically reports to a single destination
Terminal Emulation (EIA-232)	VT100 compatible
Alarm Notification	
Visual Alarm	Green, alphanumeric, dot matrix LED display; bi-color status LED
Audible Alarm	70dBA @ 2ft (0.6m); re-sound configurable (disabled, 0-24 hours—integer)
Email (Ethernet)	4 Email recipients; email sent on Alarm and Return to Normal; each alarm notifies all email recipients
SNMP Traps (Ethernet)	4 Community Strings
Logging Capabilities	
Event Log	Last 500 events
Trend Log	Cable current level every day for the last 288 days
Login Security	
Web Browser Access (Ethernet)	Web password Read Only; 1 Web password Read/Write
Terminal Emulation Access	None
Front Panel Interface	
Display	Green, alphanumeric; Avago Technologies HCMS-2973 dot matrix display
Push Buttons	Test/Reset: 1
LED Indicators	Power/Status: 1 bi-color (Power On: green; Alarm: red)
Operating Environment	
Temperature	32° to 122°F (0° to 50°C)
Humidity	5% to 95% RH, non-condensing
Altitude	15,000ft (4,572m) max.
Storage Environment	-4° to 185°F (-20° to 85°C)
Dimensions & Weight	8"W x 4.25"H x 1.25"D (203mmW x 108mmH x 32mmD); 1.5 lbs. (680g)
Mounting	Wall mountable; wall-mount enclosure LD-ENC or LD-ENC-NP (optional); rack mount bracket RMD (optional)
Certifications	CE; ETL listed: conforms to UL STD 61010-1, EN STD 61010-1; certified to CSA C22.2 STD NO. 61010-1; RoHS compliant

