

SEAHAWK ALARM PANEL



The SeaHawk LDRA6 is designed as a multi-functional alarm panel that accommodates up to six inputs. When integrated with SeaHawk Water Leak Detection Cable (SC) or spot detectors (SD-Z/SD-Z1), the LDRA6 detects the presence of any conductive fluid and alarms the appropriate zone. Additionally, each input can be configured to annunciate alarms from equipment and sensors that provide a digital dry contact signal (e.g., HVAC, PDU, UPS, generator summary/alarm contacts).

In addition to a panel summary relay output, each input has a unique relay output.

Each zone on the LDRA6 can accommodate up to 1,000 feet (305m) of SC. A Leader Cable Kit (LC-KIT) is required for the SC zone. The LDRA6 is most commonly used when there is a need to detect fluid leaks in multiple areas, and/or annunciate alarms from critical facility equipment and/or sensors.

Features

- Multi-functional panel
- Form C relay output for each input
- Adjustable leak thresholds
- Supervised inputs
- Tri-color LEDs
- Modbus RTU option (EIA-485)

Benefits

- Annunciates leak detection alarms and/or NO/NC dry contacts
- Simple integration into an existing alarm monitoring system
- Helps to prevent false/nuisance alarms
- Identifies cable disconnects and breaks
- Easily identify zone status (e.g., normal/alarm/fault)
- Conveniently integrates with Building Management Systems (BMS)

LDRA6

Specifications

Power	24VAC Isolated @ 600mA max, 50/60Hz; requires power supply: WA-AC-24 (not included) 24VDC @ 600mA max.; requires power supply: WA-DC-24-ST (not included)
Inputs	
Water Leak Detection	Compatible with SeaHawk SC or SeaHawk spot detectors (not included)
Cable Input	Each input requires SeaHawk LC-KIT: 15ft (4.57m) leader cable and EOL (not included)
Maximum Length	1,000ft (305m) per zone
Detection Response Time	20-3600sec, software adjustable in 10sec increments; ±2sec
Digital	Dry Contact NO/NC (<25mA)
Outputs	
Relay	1 Form C Summary Alarm Relay, 6 Form C alarms, one per input/zone 1A @ 24VDC, 0.5A resistive @ 120VAC; Configurable for supervised or non-supervised, latched or non-latched
Communications Ports	
EIA-232	9600 baud; Parity none; 8 data bits, 1 stop bit
EIA-485	1200, 2400, 9600 or 19,200 baud; Parity none, odd, even (programmable); 8 data bits, 1 stop bit
Protocols	
Terminal Emulation (EIA-232)	VT100 compatible
Modbus (EIA-485) - Optional	Slave; RTU Mode; Supports function codes 03, 04, 06 and 16 (Modbus optional)
Alarm Notification	
Audible Alarm	85DBA @ 2ft (0.6m); re-sound (disabled, 8, 16 or 24 hours)
Front Panel Interface	
LED Indicators	Power: 1 green (on/off); Status (1 per zone): 6 tri-color (Power On: green; Alarm: red; Cable Fault: yellow)
Push Buttons	Quiet/Test/Reset: 1
Operating Environment	
Temperature	32° to 122°F (0° to 50°C)
Humidity	5% to 95% RH, non-condensing
Altitude	15,000ft (4,572m) max.
Storage Environment	-4° to 158°F (-20° to 70°C)
Dimensions	10.5"W x 8.0"H x 2.0"D (267mmW x 203mmH x 51mmD)
Weight	4 lbs. (1.82kg)
Mounting	Wall mount enclosure
Certifications	CE; ETL listed: conforms to UL STD 61010-1, EN STD 61010-1; certified to CSA C22.2 STD NO. 61010-1; RoHS compliant



Although the information contained in this document is believed to be accurate and correct, RLE Technologies assumes no responsibility, and disclaims all liability, for any damages resulting from the use of this information or any error or omission in this document. RLE Technologies does not warrant, guarantee, or make any representations as to the performance, fitness for use, safety, or reliability of any existing or future wiring, equipment, additions or modifications to equipment, or any other component of the original or modified system. Specifications are subject to change without notice.

110041 Rev 2.3 (1/2009) ©2009 RLE Technologies



104 RACQUETTE DRIVE
FORT COLLINS CO 80524
WWW.RLETECH.COM
970 484-6510