
SPECIFICATION GUIDELINE FOR SRD Series Swing Racks

Part No.	Description	RMU
GL24SRD	24.00"H x 20.75"W x 24.00"D	12 RMU
GL36SRD	36.25"H x 20.75"W x 24.00"D	19 RMU
GL48SRD	48.50"H x 20.75"W x 24.00"D	26 RMU

General

The Wall Mount Swing Racks Deep (SRD) must be UL listed to UL60950-1 (Standard for Information Technology and Communications Equipment, Cabinet, Enclosure and Rack Systems.)
Rack shall be 19" EIA 310-E compliant.

The Wall Mount Swing Rack shall be constructed out #12 Gauge cold rolled steel (CRS). Manufacturer must be ISO 9001:2008 registered.

Common features:

- The Swing Racks will ship unassembled
- The Swing Racks shall have 22.00" of usable depth
- Rack mounting shall be tapped #10-32 on the front face
- A package of #10-32 hardware shall be included
- Weight capacity shall be 100 lbs.
- Multiple mounting provision for cable management cinch strap or wire ties
- The rack mount section will be able to swing a full 180 degrees
- Release swing rack via Allen wrench/Hex key
- Wall mounting shall be done on 16" on center using keyway holes
- Swing Racks shall be painted using durable black powder coat paint